

Serial No. 09/945,483

Amendments to the claims:

This listing of claims will replace all prior versions, and listings, of the claims in the application:

1. (Original) A method of increasing utilization of user link bandwidth for a code division multiple access communications system comprising the steps of:

selecting a set of orthogonal complex codes each having a code length that is greater than a code length of an optimum real code and less than or equal to a spreading code length; and

transferring symbols across at least one of a plurality of user links to or from at least one of a corresponding plurality of user terminals wherein the symbols are represented by a corresponding one of the set of orthogonal complex codes.

2. (Original) The method of Claim 1 wherein the set of orthogonal complex codes is generated from a Kronecker tensor product given by formula:

$$C_{L \times P} = A_L \otimes W_P$$

wherein

$C_{L \times P}$ is a matrix of orthogonal complex codes wherein each of the orthogonal complex codes has a code length equal to $L \times P$,

L is a positive integer,

P equals 2^n where n equals a positive integer,

W_P is a Walsh code matrix for a code length of P ,

A_L is a matrix of coefficients a_{jk} wherein j is a row index equal to $1 \dots L$, k is a column index equal to $1 \dots L$, and

$$a_{jk} = e^{j2\pi(j-1)(k-1)/L}.$$

3. (Original) The system of Claim 1 wherein the corresponding one of the set of orthogonal complex codes has a code length of 12.

4. (Original) The system of Claim 1 wherein the spreading code has a code length of 12.

Serial No. 09/945,483

5. (Original) A code division multiple access communications system comprising:
 a base station;
 a geo-stationary platform;
 a feeder link coupled to the base station and the geo-stationary platform for transferring symbols between the base station and the geo-stationary platform;
 a plurality of user terminals; and
 a plurality of user links coupled respectively to the plurality of user terminals and to the geo-stationary platform for transferring symbols between the geo-stationary platform and at least one of the plurality of user terminals wherein the symbols are represented by at a corresponding one of a set of orthogonal complex codes having a code length that is greater than a code length of an optimum real code and less than or equal to a spreading code length.

6. (Original) The system of Claim 5 wherein the set of orthogonal complex codes is generated from a Kronecker tensor product given by:

$$C_{L \times P} = A_L \otimes W_P$$

wherein

$C_{L \times P}$ is a matrix of orthogonal complex codes wherein the at least one of the orthogonal complex codes has a code length equal to $L \times P$,

L is a positive integer,

P equals 2^n and n equals a positive integer,

W_P is a Walsh code matrix for a code length of P ,

A_L is a matrix of coefficients a_{jk} , where j is a row index equal to $1 \dots L$, k is a column index equal to $1 \dots L$, and

$$a_{jk} = e^{j2\pi(j-1)(k-1)/L}.$$

7. (Original) The system of Claim 5 wherein the at least one of the set of orthogonal complex codes has a code length of 12.

8. (Original) The system of Claim 5 wherein the spreading code has a code length of 12.

9. (Original) A method of increasing utilization of user link bandwidth in a code

Serial No. 09/945,483

division multiple access communications system comprising the steps of:

selecting a spreading code length; and

selecting a set of orthogonal complex codes each having a code length that is greater than a code length of an optimum real code and less than or equal to the spreading code length.

10. (Original) The method of Claim 9 further comprising the step of transferring symbols across a user link to or from a user terminal wherein the symbols are represented by a corresponding one of the set of orthogonal complex codes.